



# pro clima TESCON® VANA

## Multi-Purpose Adhesive Tape

TESCON® VANA airtight sealing tape is an essential component of all air barrier systems. It is compatible with membranes, underlays as well as rigid sheathings, rigid wall underlays and rigid air barriers (RAB). TESCON® VANA is airtight and vapour permeable. It is flexible, easy to cut, and has a simple-to-remove release paper, ensuring maximum productivity during installation. TESCON® VANA provides an airtight adhesive seal to the substrate, forming excellent seals under all application conditions.

- ✓ Long-term durability (tested for 100-year adhesion\*)
- ✓ Flexible to account for building movement
- ✓ Outstanding adhesion on cold surfaces
- ✓ Thin, highly pliable and easily formed into corners and shapes
- ✓ Airtight connection for the life of the building



**Declare.**



20.03.2020



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: support@proclima.co.nz  
General: welcome@proclima.co.nz  
www.proclima.co.nz

AUSTRALIA  
1800 PRO CLIMA (776 254)  
support@proclima.com.au  
welcome@proclima.com.au  
www.proclima.com.au





# pro clima TESCON® VANA

## Multi-Purpose Adhesive Tape

### Technical Data

Carrier material:	special fleece made from PP
Release material:	siliconised paper
Temperature resistance:	long term -40 °C to +90 °C
Installation temperature:	from -10 °C
UV stability and outdoor exposure:	indoor use only
Colour:	dark blue
Storage:	cool and dry

\*solid acrylate adhesive used on TESCON® VANA tested for 100-year adhesion <https://proclima.com/service/100-years-adhesion>

### IMPORTANT INFORMATION

- Long-term durability (tested for 100-year adhesion\*).
- Thin, highly pliable and easily formed into corners and shapes.
- Outstanding adhesion in cold conditions.
- Can be used to seal penetrations in INTELLO®.

### PRODUCT DESCRIPTION

TESCON® VANA is a multi-purpose adhesive tape which forms an essential part of your air barrier system. Made from polypropylene with acrylate it has excellent workability and adhesion for secure and permanent airtight seal of overlaps between INTELLO®, joints between membranes and smooth, non-mineral surfaces. Also suitable for sealing joints between wood based materials.

### WEATHER EXPOSURE

This product is not designed for external use but will handle some direct exposure to UV and still fulfil the intended use for air control. Envelope and reveal details should be detailed to prevent direct sunlight onto the TESCON® VANA in service.

### APPLICATION NOTES

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal.

For special applications such as installation in corners of windows or doors consider TESCON® PROFIL which comes in a 60 mm width with a split 10 mm side strip.

Delivery Form				
ID CODE	LENGTH	WIDTH	BACKING	QTY
12185	30 m	60 mm	No split	10
11365	30 m	60 mm	No split	20 <b>big pack</b>



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)

